

TP6/V/1

CUTTING BENDING MACHINE FOR AXIAL COMPONENTS VERTICAL MOUNTING

EXAMPLES OF FORMS



80.0LO1 STANDARD



The TP6/V machine is designed for cutting and bending taped axial components for vertical mounting. It operates components with lead diameters from 0,5 to 0,8mm (.019 to .031"). The bending pitch is determined by the bending cam supplied and it can be changed by replacing this cam with one having different thickness.

WARNING: FOR PITCH 2,54 MM MINIMUM LENGTH BETWEEN BODY AND TAPE SHALL BE: LENGTH OF THE BODY PLUS 12 MM. THE LENGTH OF THE LEAD FOR THE LARGER PITCHES SHALL BE INCREASED BY RELATION

PRODUCTION:
TAPED: 50.000
LOOSE: 5.000


TP6/V/1 STANDARD VERSIONS

80.OL01 - PITCH 2,54 MM




	MM		IN	
	min	max	min	max
A	2	6	.078	.236
L		15		.590
F	3	8	.118	.314
D	0,5	3	.019	.118
d	0,5	0,8	.019	.031
P	2,54 fix		.1 fix	

80.OL03 - PITCH 3,8 MM




	MM		IN	
	min	max	min	max
A	2,5	6	.098	.236
L		15		.590
F	3	8	.118	.314
D	0,5	5	.019	.196
d	0,5	0,8	.019	.031
P	3,8 fix		.15 fix	

80.OL04 - PITCH 5,08 MM



	MM		IN	
	min	max	min	max
A	3	7	.118	.275
L		15		.590
F	3	8	.118	.314
D	0,5	8	.019	.314
d	0,5	0,8	.019	.031
P	5,08 fix		.2 fix	

80.OL05 - PITCH 7,62 MM



	MM		IN	
	min	max	min	max
A	4	7	.157	.275
L		15		.590
F	3	8	.118	.314
D	0,5	10	.019	.393
d	0,5	0,8	.019	.031
P	7,62 fix		.3 fix	

TP6/V/21

CUTTING BENDING MACHINE FOR AXIAL COMPONENTS VERTICAL MOUNTING

EXAMPLES OF FORM



80.OL21 REINFORCED




The TP6/V/21 machine is designed for cutting and bending taped axial components for vertical mounting. It operates components with lead diameters from 0,8 to 1,3mm (.031 to .051"). The bending pitch is determined by the bending cam supplied and it can be changed by replacing this cam with one having a different thickness.

WARNING: FOR PITCH 3,8 MM MINIMUM LENGTH BETWEEN BODY AND TAPE SHALL BE: LENGTH OF THE BODY PLUS 16 MM. THE LENGTH OF THE LEAD FOR THE LARGER PITCHES SHALL BE INCREASED BY RELATION

PRODUCTION:
TAPED: 50.000
LOOSE: 5.000


TP6/V/21 STANDARD VERSIONS

80.OL21 - PITCH 3,8 MM




	MM		IN	
	min	max	min	max
A	4	9	.157	.354
L		15		.590
F	3	8	.118	.314
D	0,8	5	.031	.196
d	0,8	1,3	.031	.051
P	3,8 fix		.15 fix	

80.OL22 - PITCH 5,08 MM



	MM		IN	
	min	max	min	max
A	5	9	.196	.354
L		15		.590
F	3	8	.118	.314
D	0,8	8	.031	.314
d	0,8	1,3	.031	.051
P	5,08 fix		.2 fix	

80.OL23 - PITCH 7,62 MM



	MM		IN	
	min	max	min	max
A	6	9	.235	.354
L		15		.590
F	3	8	.118	.314
D	0,8	10	.031	.393
d	0,8	1,3	.031	.051
P	7,62 fix		.3 fix	

TP6/V OPTIONAL ACCESSORIES



BR6 - 400200 400200 REEL HOLDER



MOT98 - 7915030 - 220 V. - MOTOR DRIVE UNIT

MOT98 - 7915031 - 110 V - MOTOR DRIVE UNIT



TNS - 21.0011 WASTE TAPE EJECTOR



CS30 - 51.0300 FEEDER FOR LOOSE COMPONENTS



800240 COMPLETE BODY GUIDE
